

T 1    

Kapacitet /

Capacità 1 kolica 20 ladica / 1 carrello 20 teglie
GN 2/1 - EN 600×800 2
kolica 20 pladnjeva / 2 carrelli 20 teglie
GN 1/1 - EN 600×400

Radna temperatura / Temperatura di
esercizio -40/+85 °C

Brzo hlađenje / Resa

abbattimento 90°C + 3°C u 90' = 220 Kg

Brzo zamrzavanje / Brzo zamrzavanje

90°C - 18°C za 240 minuta = 170 kg

Hladnjak / Klaonica

230 V / 1 faza / 50-60 Hz - 0,88 kW / 4,79 A

Udaljena jedinica / Unità remota

400 V / 3 faze / 50 Hz - 11,9 kW / 21,7 A

Rashladni kapacitet / Rashladna

snaga (-10°C/+45°C) = 17800

W (-40°C/+45°C) = 3600 W

Vanjske mjere / Dimensioni esterne

D 1480 P/D 1352 V 2340 mm

Unutarnje dimenzije / Dimensioni interne


D 880 P/D 1038 V 1970 mm

Unesi razmak / Luce porta

D 880 V 1970 mm

Rashladno sredstvo/plinsko rashladno sredstvo

R452a (GWP 2141)



T2    

Kapacitet /

Capacità 2 kolica 20 ladica / 2 carrelli 20 teglie GN
2/1 - EN 600×800

Radna temperatura / Temperatura di
esercizio -40/+85 °C

Brzo hlađenje / Resa

abbattimento 90°C + 3°C u 90' = 460 Kg

Brzo zamrzavanje / Brzo zamrzavanje

90°C - 18°C za 240 minuta = 360 kg

Hladnjak / Klaonica

230 V / 1 faza / 50-60 Hz - 1,76 kW / 9,58 A

Udaljena jedinica / Unità remota

400 V / 3 faze / 50 Hz - 23,1 kW / 41,7 A

Rashladni kapacitet / Rashladna

snaga (-10°C/+45°C) = 38700

W (-40°C/+45°C) = 8300 W

Vanjske mjere / Dimensioni esterne

D 1480 P/D 2562 V 2340 mm

Unutarnje dimenzije / Dimensioni interne

D 880 P/D 2134 V 1970 mm

Unesi razmak / Luce porta

D 880 V 1970 mm

Rashladno sredstvo/plinsko rashladno sredstvo

R452a (GWP 2141)



T3    

Kapacitet /

Capacità 3 kolica 20 pladnjeva / 3 carrelli 20 teglie GN
2/1 - EN 600×800

Radna temperatura / Temperatura di
esercizio -40/+85 °C

Brzo hlađenje / Resa

abbattimento 90°C + 3°C u 90' = 660 Kg

Brzo zamrzavanje / Brzo

zamrzavanje 90°C - 18°C u 240 minuta = 500 kg

Hladnjak / Klaonica

400 V / 3 faze / 50-60 Hz - 2,65 kW / 4,76 A

Udaljena jedinica / Unità remota

400 V / 3 faze / 50 Hz - 31,7 kW / 54,6 A

Rashladni kapacitet / Rashladna

snaga (-10°C/+45°C) = 53200

W (-40°C/+45°C) = 12100 W

Vanjske mjere / Dimensioni esterne

D 1480 P/D 3642 V 2340 mm

Unutarnje dimenzije / Dimensioni interne

D 880 P/D 3214 V 1970 mm

Unesi razmak / Luce porta

D 880 V 1970 mm

Rashladno sredstvo/plinsko rashladno sredstvo

R452a (GWP 2141)



Wi-Fi opcionalno
Wi-Fi opcionalno



Peciva
Pasticceria



Gelato
Gelateria




Catering
Ristorante



Pekara
Panificia

Specifikacije Šokera/Brzih hladnjaka zamrzivača

Speciche degli abbattitori di temperatura/surgelatori rapidi



T4



Kapacitet /

Capacità 4 kolicia 20 ladica / 4 carrelli 20 teglie GN 2/1 - EN 600×800

Radna temperatura / Temperatura di esercizio -40/+85 °C

Brzo hlađenje / Resa

abbattimento 90°C + 3°C u 90' = 800 Kg

Brzo zamrzavanje / Brzo

zamrzavanje 90°C - 18°C u 240 minuta = 600 kg

Hladnjak / Klaonica

400 V / 3 faze / 50-60 Hz - 3,53 kW / 6,35 A

Udaljena jedinica / Unità remota

400 V / 3 faze / 50 Hz - 39,63 kW / 68,25 A

Rashladni kapacitet / Rashladna

snaga (-10°C/+45°C) = 66500

W (-40°C/+45°C) = 16000 W

Vanjske mjere / Dimensioni esterne

D 1480 P/D 4722 V 2340 mm

Unutarnje dimenzije / Dimensioni interne


D 880 P/D 4294 V 1970 mm

Unesi razmak / Luce porta

D 880 V 1970 mm

Rashladno sredstvo/plinsko rashladno sredstvo

R452a (GWP 2141)



T5



Kapacitet /

Capacità 5 kolicia 20 ladica / 5 carrelli 20 teglie GN 2/1 - EN 600×800

Radna temperatura / Temperatura di esercizio -40/+85 °C

Brzo hlađenje / Resa

abbattimento 90°C + 3°C u 90' = 1000 Kg

Brzo zamrzavanje / Brzo

zamrzavanje 90°C - 18°C u 240 minuta = 750 kg

Hladnjak / Klaonica

400 V / 3 faze / 50-60 Hz - 4,41 kW / 7,94 A

Udaljena jedinica / Unità remota

400 V / 3 faze / 50 Hz - 46,36 kW / 79,85 A

Rashladni kapacitet / Rashladna

snaga (-10°C/+45°C) = 77800

W (-40°C/+45°C) = 16400 W

Vanjske mjere / Dimensioni esterne

D 1480 P/D 5802 V 2340 mm

Unutarnje dimenzije / Dimensioni interne


D 880 P/D 5374 V 1970 mm

Unesi razmak / Luce porta

D 880 V 1970 mm

Rashladno sredstvo/plinsko rashladno sredstvo

R452a (GWP 2141)



T6



Kapacitet /

Capacità 6 kolicia 20 ladica / 6 carrelli 20 teglie GN 2/1 - EN 600×800

Radna temperatura / Temperatura di esercizio -40/+85 °C

Brzo hlađenje / Resa

abbattimento 90°C + 3°C u 90' = 1000 Kg

Brzo zamrzavanje / Brzo

zamrzavanje 90°C - 18°C u 240 minuta = 750 kg

Hladnjak / Klaonica

400 V / 3 faze / 50-60 Hz - 5,29 kW / 9,53 A

Udaljena jedinica / Unità remota

400 V / 3 faze / 50 Hz - 46,36 kW / 79,85 A

Rashladni kapacitet / Rashladna

snaga (-10°C/+45°C) = 77800

W (-40°C/+45°C) = 16400 W

Vanjske mjere / Dimensioni esterne

D 1480 P/D 6882 V 2340 mm

Unutarnje dimenzije / Dimensioni interne

D 880 P/D 6454 V 1970 mm

Unesi razmak / Luce porta

D 880 V 1970 mm

Rashladno sredstvo/plinsko rashladno sredstvo

R452a (GWP 2141)